TEAM ENGINEERING & MANAGEMENT, INC.

August 2, 2010

Dr. Bob Harrington Inyo County Water Department 135 South Jackson Street Independence, CA 93526

RE: Summary of Hydrologic Monitoring Activities July 2010 Rose Valley, Inyo County, California Hay Ranch Project Conditional Use Permit #2007-03

Dear Dr. Harrington:

This letter is intended to summarize hydrologic monitoring activities conducted in July 2010 by TEAM Engineering & Management, Inc. (TEAM), related to the Hay Ranch Water Extraction Project and CUP #2007-03.

Phase 2: Startup Monitoring and Reporting

With the initiation of pumping by Coso Operating Company on December 25, 2009, the Hay Ranch Water Extraction Project entered into the Phase 2 Startup Monitoring and Reporting period as outlined in the Hydrologic Monitoring and Mitigation Plan (HMMP).

During the July 2010 monthly hydrologic data collection event, static depth-to-water (DTW) measurements, one visual observation of the Little Lake Ranch Siphon Well Outflow and four sets of flow rates were collected by TEAM from 30 monitoring locations in the Rose Valley area, as summarized in the attached table (Table 1). Data for this monthly field event was collected on July 21-22. Pressure transducer data were downloaded from 24 units, including one "BaroTroll" measuring barometric pressure. On July 6, a DTW measurement at LADWP 816 Well was taken by LADWP personnel.

In May 2010, Coso Operating Company completed installation of a permanent water tank between the Hay Ranch North and South Wells and subsequently removed the temporary groundwater holding tank and associated infrastructure. With the completion of the permanent tank, groundwater flow from the Hay Ranch South Well is being recorded by a new totalizer; "HRS B Totalizer" measures Hay Ranch South flow into the permanent water tank. This totalizer went on-line May 12, 2010 with an initial reading of 0 gallons. The existing totalizer "HRS A Totalizer" which has been capturing all flow previously pumped from the Hay Ranch South Well was removed. The amount of groundwater captured by HRS A for the Hay Ranch Project was 245,294,000 gallons (753 acre feet). The Hay Ranch North Well, the project's reserve production well, was pumped for the first time since project initiation in early July, a totalizer for groundwater pumped from this well has been installed at the new permanent tank, HRN C Totalizer with an initial reading of 0 gallons.

The HRS B Totalizer read 131,240,000 gallons at 10:32, July 21. The HRN C Totalizer read 8,443,000 gallons at 10:31, July 21. The combined totals from HRS A, HRS B, and HRN C represent approximately 384,977,000 gallons (1182 acre feet) of groundwater extracted from the Hay Ranch property wells since project initiation on December 25, 2009.

Figure 1 presents the combined amount of groundwater pumped from the Hay Ranch North and South wells in acre feet (AF) with a hypothetical pumping amount. The hypothetical pumping amount assumes a linear pumping rate (approximately 8.2 AF/day) which starts on December 25, 2009 and reaches 3000 AF on December 25, 2010.

Dunmovin Trigger Level

In Table 3.1 of the HMMP for the Hay Ranch Project, Trigger Levels have been set for the 0.5year time period at specific monitoring wells. Approximately seven months (0.58 years) have elapsed since the Hay Ranch Project's pumping was initiated. Based on data collected by TEAM during the July 21-22 monitoring event, the groundwater elevation (GWE) in the Dunmovin Well continues to be below 0.5-year Trigger Level (Table 2).

The baseline groundwater elevation (GWE) for Dunmovin, set by Inyo County Water Department (ICWD) in January 2010, is 3252.73 feet. The GWE at Dunmovin as measured at 9:00 on July 21 was 3252.10 feet. The 0.5-year Trigger Level for Dunmovin is 0.3 feet. The Dunmovin GWE has decreased by 0.63 feet compared to its baseline, exceeding its Trigger Level drawdown by 0.33 feet. The Dunmovin GWE was 2.17 feet above its Maximum Acceptable Drawdown level. The maximum GWE recorded at Dunmovin Well was 3253.60 and occurred on January 21, 2010. The minimum GWE recorded at the Dunmovin Well was 3252.07 and occurred on September 16, 2009. Inyo County Water Department and Coso Operating Company were notified by TEAM in a timely manner regarding this continuing trigger level event.

Groundwater elevations are above 0.5-year Trigger Levels and above Maximum Acceptable Drawdowns at all other Hay Ranch Project monitoring wells which have baseline and trigger levels established.

Operational Notes

The Davis Ranch South Flow flume is experiencing minor sedimentation due to biological activity. This flume is being cleaned during each monthly field event and a corrective solution to this sedimentation issue is being devised. This sedimentation is causing the pressure readings from the transducer installed at Davis Ranch South Flow to drift upwards during the monthly data collection periods.

Also, the Little Lake Ranch North pressure transducer generated erroneously high pressure data during the June-July monitoring period. The pressure transducer appeared to stabilize in July. This transducer will be examined before the next monthly field event and be repaired or replaced, if necessary.

Data Transmittal

TEAM posted updates to the "Coso" database on the ICWD web server. New Hay Ranch Project hydrographs in PDF form were uploaded to the ICWD website. TEAM also submitted the *Dunmovin Well Assessment Report* to ICWD.

* * * * * *

If you have any questions or require additional information, please contact TEAM at your convenience.

Sincerely,

TEAM Engineering & Management, Inc.

Keith Rainville Staff Geologist

S:\Coso.HR Monitoring Summary_July_10

TABLE 1Field Observations of Rose Valley Hydrologic Monitoring PointsJuly 21-22, 2010

Project Name:	Hay Ranch Project HMMP	Date: July 21-22, 2010		
Location:	Rose Valley, Inyo County			
Observer(s):	K. Rainville	Page: 1 of 1		

Well ID	Monitoring Point	Date	Time	DTW	Flow	GWE	Method	Transducer	Notes
				(ft)	(cfs)	(ft amsl)		Log Interval	
RV-10	Dews	07/21/10	12:45	231.33		3755.59	TEAM manual read	NA	1
RV-20	LADWP 816	07/06/10	11:08	78.51		3436.55	LADWP manual read	NA	Data provided by LADWP
RV-30	Cal Pumice	07/21/10	9:25	248.70		3257.19	TEAM manual read	Hourly	
RV-40	Dunmovin	07/21/10	9:00	295.77		3252.10	TEAM manual read	NA	
RV-50	Hay Ranch North	07/21/10	10:31	NM	No	NM	TEAM manual read	NA	8,443,000 gallons (26 AF) pumped since 12/25/09
RV-60	Hay Ranch 1A	07/21/10	10:39	193.64		3238.53	TEAM manual read	Hourly	
RV-61	Hay Ranch 1B	07/21/10	10:43	204.46		3227.39	TEAM manual read	Hourly	
RV-62	Hay Ranch 1C	07/21/10	10:48	196.06		3235.44	TEAM manual read	Hourly	
RV-70	Hay Ranch South	07/21/10	10:32	NM	Yes	NM	TEAM manual read	NA	376,534,000 gallons (1156 AF) pumped since 12/25/09
RV-80	Hay Ranch 2A	07/21/10	10:17	195.89		3237.11	TEAM manual read	Hourly	
RV-81	Hay Ranch 2B	07/21/10	10:13	209.70		3222.93	TEAM manual read	Hourly	
RV-82	Hay Ranch 2C	07/21/10	10:23	198.08		3234.02	TEAM manual read	Hourly	
RV-90	Coso Jct Ranch	07/21/10	9:39	171.38		3231.75	TEAM manual read	Hourly	
RV-100	Coso Jct Store #1	07/21/10	9:51	143.21		3228.91	TEAM manual read	Hourly	
RV-110	Davis Ranch North Well	07/21/10	12:02	6.47		3886.53	TEAM manual read	Hourly	
RV-111	Davis Ranch South Well	07/21/10	12:13	11.25		3886.75	TEAM manual read	Hourly	
RV-112	Davis Ranch South Flow	07/21/10	12:21	NA	0.012	NA	TEAM manual read	Hourly	
RV-120	Red Hill Well (BLM)	07/21/10	11:08	140.02		3200.81	TEAM manual read	Hourly	
RV-130	G-36	07/22/10	12:40	180.04		3199.98	TEAM manual read	NA	
RV-140	Lego	07/22/10	12:32	222.13		3200.72	TEAM manual read	Hourly	
RV-150	Cinder Road	07/21/10	11:35	190.96		3187.00	TEAM manual read	Hourly	
RV-160	18-28 GTH	07/22/10	12:21	173.98		3188.60	TEAM manual read	Hourly	
RV-170	Fossil Falls Campground	07/22/10	13:12	140.95		3175.82	TEAM manual read	NA	
RV-180	LLR North Well	07/22/10	9:34	40.06		3159.04	TEAM manual read	Hourly	
RV-210	LLR Dock Well	07/22/10	10:05	6.39		3147.75	TEAM manual read	Hourly	
RV-220	LLR Stilling Well (lake surface)	07/22/10	10:20	3.88		3147.16	TEAM manual read	Hourly	
RV-230	LLR Little Lake Outflow	07/22/10	11:12	NA	0.00	NA	TEAM manual read	Hourly	
RV-240	LLR Coso Springs Flow	07/22/10	10:57	NA	0.28	NA	TEAM manual read	Hourly	
RV-245	LLR North Culvert Flow	07/22/10	11:50	NA	0.71	NA	TEAM manual read	Hourly	
RV-250	LLR Siphon Discharge	07/22/10	11:25	NA	Yes	NA	TEAM visual read	NA	Discharging into Pond 2; increased flow from 6/18/10
RV-260	LLR Hotel Well	07/22/10	13:22	0.91		3137.87	TEAM manual read	Hourly	Pressure gauge reads 0 psi

NM - not measured; NA - not applicable; IO - Inoperative

DTW - Depth to water in feet below top of casing or other reference point; a negative DTW indicates that the groundwater elevation is above the surveyed reference point

GWE- Groundwater elevation in feet above mean sea level

TABLE 2 Hay Ranch Project Groundwater Baselines and Trigger Levels July 2010

Well ID	Monitoring Point	Baseline GWE*	Recent Date	Recent GWE	Recent GWE	Recent GWE	Trigger Level	Recent GWE
					Compared to Baseline	Above Max DD**	At .5 year elapsed	Compared to Trigger Level
RV-30	Cal Pumice	TBD***	7/21/10	3257.19	NA	NA	1.30	NA
RV-40	Dunmovin	3252.73	7/21/10	3252.10	-0.63	2.17	0.30	-0.33
RV-90	Coso Jct Ranch	3230.65	7/21/10	3231.75	1.10	3.60	0.40	1.50
RV-100	Coso Jct Store #1	3227.59	7/21/10	3228.91	1.32	3.62	0.30	1.62
RV-120	Red Hill Well	3200.66	7/21/10	3200.81	0.15	TBD****	TBD****	NA
RV-130	G-36	3198.35	7/22/10	3199.98	1.63	2.73	0.20	1.83
RV-140	Lego	3199.21	7/22/10	3200.72	1.51	2.61	0.20	1.71
RV-150	Cinder Road	3186.92	7/21/10	3187.00	0.08	0.78	0.20	0.28
RV-160	18-28 GTH	3187.67	7/22/10	3188.60	0.93	1.93	0.20	1.13
RV-180	LLR North Well	3158.88	7/22/10	3159.04	0.16	0.56	0.20	0.36

GWE Groundwater elevation in feet above mean sea level


* Baseline groundwater elevations set 1/25/10 and approved by Inyo County Water Department

** Max DD: Maximum Acceptable Drawdown from HMMP Table 3-1

*** Cal Pumice Well baseline groundwater elevation has not been set

**** Trigger Levels and Maximum Acceptable Drawdown levels for Red Hill Well have not been set

FIGURE 1 HYPOTHETICAL AND ACTUAL HAY RANCH PROJECT PUMPING



The "linear pumping rate" shown above is a hypothetical pumping rate that reaches 3000 Acre Feet (AF) in one year with pumping evenly distributed at 8.2 AF/day.

ENGINEERING & MANAGEMENT, INC. Bishop and Mammoth Lakes, California

7/26/2010